



# FTX290

## 290 HP Mulching Tractor







**fecon.com**  
**sales@fecon.com**  
**+1 513 696 4430**

GENERAL	FTX290
Standard Bull Hog®	BH120
Overall Height	114" / 2884 mm
Length of Tractor Only	185" / 4680 mm
Length with BH120	238" / 6021 mm
Length with BH120 and Winch	256" / 6477 mm
Weight of Tractor Only	23300 lbs / 10569 kg
Weight of Standard Bull Hog (BH120)	4950 lbs / 2245 kg
Weight with BH120 and Winch	29800 lbs / 13517 kg
Width of Tractor Only	90" / 2280 mm
Width with BH120	100" / 2533 mm
ENGINE	
Make / Model	Cummins QSC 8.3 Tier III
Horsepower	290 hp / 216 kw
Maximum Rated Torque	895 ft lbs @ 1500 rpm
Maximum RPM	2200
Reversing Engine Fan	Standard
Cooling	Water Cooled
Fuel Consumption	14 - 18 gph
Fuel Tank	115 gal / 435 ltr
Hydraulics	
Hi-Flow Circuit PSI/GPM	5510 psi / 101 gpm
Low Flow Circuit PSI/GPM	3000 psi / 26 gpm
Hydraulic Reservoir	65 gal / 246 ltr
Loader Maximum Capacity	8000 lbs
UNDERCARRIAGE	
Type	Steel with Single Grouser
Track Gauge	60" / 1524 mm
Track Width	30" / 800 mm
Ground Pressure (SAE J1309)	3.3
Ground Clearance	19" / 482 mm
Travel Speed (low/hi)	0-4.7 mph / 0-8.7 kph

### Optional Equipment

- Hydraulic Winch 15,000 lbs
- Espar Engine and Hydraulic Heater
- 1 1/8" Polycarbonate Windshield
- Triple Grouser Track Shoes



Large engine doors put all components and daily checks in easily reached positions. Transfer pump mounted on board will keep oil clean when servicing.



Cleaning and periodic services are performed quickly on the FTX290. Tanks are equipped with large clean out ports for thorough draining and cleaning.



Wide rear door access to cooler, radiator and reversing fan. Exhaust and intake are well guarded from debris and the elements.



The FTX290 cab offers legroom and comfort with standard adjusting suspension seat. Two side doors and standard roof hatch safely provides three points of egress. Windows are a polycarbonate material on all sides with optional thickness to meet local regulations. On board diagnostics allow operators system control for maximum production and efficient management of power. The FTX290 is sized for large scale work and fits into the tighter jobsites as well as being a legal load in most areas.



- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection meet your job safety requirements.
- Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights are subject to vary based on options. • Safety Is The Responsibility Of The Operator.
- Specifications subject to change without notice. • Pictures may contain optional accessories.
- Photographs may have been altered for marketing purposes.

